Press Die Sets				
	QDS 263 B QDS B-8-RA			
SH 2 M Ecoline SH 2 M H2, SH 2 P, SH 2 A, SH 2 LA		47-71	Package: Machine + PB Ø 14, 17, 20, 24 + QDS 26X B Package: Machine + PB Ø 14, 17, 20, 24, 28, 32, 40	
	QDS 239 B	QDC 239.5	+ QDS 26X B	
HM 200, SC 3, SH 4			Package: Machine + PB Ø 17, 20, 24, 28, 32, 40, 44, 47, 50 + QDS 239 B + QDC 239.5	
SC 4		(0)	Package: Machine + PB Ø 17, 20, 24, 28, 32, 36, 40, 44, 47, 54, 62 + QDS 239 B + QDC 239.5	
SH 7, SC 6, SH 6, SH 6 S			Package: Machine + PB 17, 20, 24, 28, 32, 40, 44, 50, 57, 71 + 265.239 L + QDS 239 B + QDC 239.5	
SH 10 i, SH 10 i XL			Package: Machine + PB Ø 17, 20, 24, 28, 32, 40, 44, 50, 57, 71 + 237.239.2L2 + QDS 239 B + QDC 239.5	
SC 12 i			Package: Machine + PB Ø 17, 20, 24, 28, 32, 40, 44, 50, 57, 71 + 237.239.2L2 + QDS 239 B + QDC 239.5	

PUM 0.8/3.2-700 bar

The mobile high-pressure power unit manages 700 bar: a real magic box!

UNIFLEX mobile hydraulic power packs are popular worldwide due to their high performance, robustness and compact dimensions.worldwide. With an innovative high-pressure power unit, UNIFLEX now offers a practical accessory, namely an ingeniously simple external power tool: with a standard cordless screwdriver (min. 25 Nm drive torque), manual workshop presses for 1" hoses (4SH/R15) can be driven hydraulically.



PUU

The PUU is a hydraulic unit with an oil delivery capacity of 10 l/min at 28 MPa/280 bar.

This compact system with integrated 35 I oil tank fits perfectly with our HM 200 or can be used flexibly in other ways.



Technische Daten	РИМ	PUU
Max. pressure	70 MPa (700 bar)	28 MPa (280 bar)
Nominal pressure	70 MPa (700 bar)	28 MPa (280 bar)
Adjustable pressure relief valve	up to 700 bar manually adjustable	-
Drive	All commercially available cordless screwdrivers (min. 25Nm)	1-3 phases 2,2-3 KW
Temperature range	10°C to +35°C	-
Shoulder strap	✓	-
Oil tank volume	2,5	35 I (Ölvolumen)
Pressure gauge measuring connection	✓	-
Delivery rate	3.2 L/min Low pressure up to 5 MPa (50 bar)0.8 L/min High pressure above 5 MPa (50 bar)	10 I/min (max.)
L x W x H (mm)	245 x 170 x 220	300 x 450 x 550
Weight	8.5 kg with oil	33 kg