



The P 250 / P 260 Test Bench with Control IPC are new modular test benches that can be adapted to your needs. They offer the possibility to test with the Steck-o, Hand or Hydraulic quick cone system. You can also install a Euro Pallet inside for the P 250 / P 260. The Chamber also accepts a non-end extension if you prefer to test a hose lengthwise (only P 250). The controller offers all parameters for a fully automatic test, with visualization of the pressure and may other features but also connectivity to your server or other machine in line with industry 4.0. or IoT.



P 250 with one hand clamping



P 260 with four hand clampings



P 250



P 260

Technical Data	P 250	P 260 NEW
Test pressure	150 - 1,500 bar / 2,175 - 21,750 psi	150 - 1,500 bar / 2,175 - 21,750 psi
Control	IPC	IPC
Drive	oscillating intensifier	oscillating intensifier
Flow (effective)	7.5 l/min	7.5 l/min
Capacity	7 bar, 100 NI/min	7 bar, 100 NI/min
Anticorrosion additive	Water-oil emulsion EM-CO 18kg	Water-oil emulsion EM-CO 18kg
Tank dimensions mm (inch)	2,194 x 890 x 470 mm (86" x 35" x 18.5")	2,194 x 890 x 1,100 mm (86" x 35" x 43.3")
Test bench dimensions mm (inch)	2,700 x 1,450 x 1,550 mm (106" x 57" x 61")	2,700 x 1,450 x 2,100 mm (106" x 57" x 82.7")
Reservoir capacity	120 l	120 l
Loading	250 kg	250 kg
Weight	570 kg	900 kg
Noise level	75 dBA	75 dBA
Capacity electric	3 VAC	3 VAC
Steck-O	✓	✓
Options		
High pressure	150 - 3,000 bar / 2,175 - 43,500 psi	150 - 4,500 bar / 2,175 - 65,250 psi
Low pressure	20 - 1,500 bar / 290 - 21,750 psi	20 - 1,500 bar / 290 - 21,750 psi
Stainless steel tank optional	✓ Standard no VA	-
Extended version on request L x W x H mm (inch)	2,220 x 1,000 x 1,400 (87.4" x 39.4" x 55.11")	-
Weight	420 kg	-
VA	✓	✓
Hand clamping	4 Lines	4 Lines

Steck-O up to 1.500 bar / Hand or hydraulic clamping up to 3.000 bar

P 250:

Steck-O adapter and screw connection:

- 1 x Steck-O up to 1500 bar: 414.1000
- 4 x Steck-O up to 1500 bar: 414.1012
- 1 x Screw connection up to 3000 bar: 414.1008
- 4 x Screw connection up to 3000 bar: 414.1013

P 250:

Fast clamping system:

- 1 x Hand clamping up to 1500 bar: 414.1002
- 3 x Hand clamping up to 1500 bar: 414.1032
- 1 x Hand clamping up to 3000 bar: 414.1005
- 3 x Hand clamping up to 3000 bar: 414.1035

P 260:

Steck-O adapter and screw connection:


- 1 x Steck-O up to 1500 bar: 415.1100
- 4 x Steck-O up to 1500 bar: 415.1104
- 1 x Screw connection up to 4500 bar: 415.1181
- 4 x Screw connection up to 4500 bar: 415.1184

P 260:

Fast clamping system:

- 1 x Hand clamping up to 1500 bar: 415.1121
- 4 x Hand clamping up to 1500 bar: 415.1124
- 1 x Hand clamping up to 3000 bar: 415.1151
- 4 x Hand clamping up to 3000 bar: 415.1154

Description



Axially adjustable quick-change system with adjustable rotating head.



Sealing tips for hand clamping.



Extension of quick system to 2 lines.



Barcode Scanner BCR CTR2C-Kit