



The UNIFLEX KS 6, KS 8 and KS 10 are designed for precision crimping and calibration.



KS 6, KS 8, KS 10

Technical Data	KS 6 <b>NEW</b>	KS 8	KS 10
Crimp force (kN/Ton)	500/50	800/80	1,800/180
No grease: 20% less friction	✓	✓	✓
Control	Control C.2	Control C.2	Control C.2
Max. Crimp range	55 mm	139 mm	139 mm
Opening	+27.5 mm	+45 mm	+45 mm
Opening without dies	91.5 mm	190 mm	190 mm
Type of dies	PBK 266	PBK 237	PBK 237
Speed (mm/sec)			
Close	12	7	3.5
Crimp	12	7	3.5
Open	30	15	6
Noise level	58 dBA	58 dBA	58 dBA
Drive	5.5 kW 3 VAC	5.5 kW 3 VAC	5.5 kW 3 VAC
Oil	80 l	80 l	80 l
L x W x H (mm)	1,000 x 1,000 x 1,700	1,000 x 1,000 x 1,700	1,000 x 1,000 x 1,700
Weight	470 kg	570 kg	570 kg

Type of dies	
PBK 266	
Ø mm	mm
6.8	3
8	3
9	3
10	3
11	3
12	3
14	4
16	4
17	4
19	4
20	4.5
22	4.5
24	4.5
25	4.5
28	5
30	5
32	5
34	5
36	5
39	5
40	5
44	5
47	5

Type of dies	
PBK 237	
Ø mm	mm
12	3
14	3
16	4
19	4
22	4.5
24	4.5
26	4.5
28	4.5
32	5
36	5
40	5
44	5
47	5
50	5
54	5
57	5
62	5
67	5
71	5
74	5
78	5
84	5
86	5
90	5
96	5
103	5
106	5